



FULL MOON RECESSED

FULL MOON RECESSED



DESCRIPTION

Available in RGBW and white light configurations, FULL MOON Recessed is the ideal in-ground solution for creating elegant wall-grazing effects in residential and hospitality environments, as well as for the distinctive illumination of landscape features. Working with a remote PSU, it is available in two walk-on versions featuring either a stainless-steel frame or a flush-mounted full-glass finish for a refined, minimalist appearance with no visible screws. A robust drive-over version, distinguished by a larger flange and a load-bearing capacity of up to 2,000 kg, is also available for installation in vehicular areas.


MAIN FEATURES

- Max. delivered lm output: 1498 lm / 120 lm/W
- Max. size: $\varnothing$ 112x 94mm / $\varnothing$ 4.4"x 3.7"
- Control system: DMX-RDM, DALI, ON-OFF, 0-10V with remote PSU
- Medium-size in-ground LED uplighter or wall-grazing applications, available for both pedestrian and vehicular areas.


LED COLOUR CONFIGURATIONS




FULL MOON RECESSED



DRIVE.OVER



FRAME



ALL-GLASS

FEATURES



DMX - RDM



DALI



ON - OFF



0 - 10 V



CLASS



WALK OVER



DRIVE OVER



IP68



IK09
IK10



0.9 KG



OPTIONS



ANTI-SLIP



ETL PENDING

LED COLOUR CONFIGURATIONS



RGB+W
3000K



RGB+W
4000K



2200K



2700K



3000K



4000K

CODES

AL5418 FULL MOON RECESSED
AL5419 FULL MOON RECESSED 48V

PERFORMANCE	WATT	MAX LM OUTPUT	LM/WATT
FULL MOON REC. RGBW	13	475	37
FULL MOON REC. W	12.5	1498	120
FULL MOON REC. W 48V	13.5	1498	111

BEAM ANGLE REFERENCE	RGBW	W
SPOT	12°	-
NARROW	22°	18°
MEDIUM	33°	25°
WIDE	55°	35°
EXTRA WIDE	-	50°
ELLIPTICAL	13° x 48°	22° x 65°°

MORE INFO

on GRIVEN ESSENTIALS' website

