MOON RECESSED SERIES



DESCRIPTION

MOON RECESSED and MOON RECESSED ADJUSTABLE are the perfect solution for marking out paths, walkways, and entrances, as well as for a distinctive illumination of small architectural or landscape elements. Featuring a shallow recess depth for a hassle-free installation, this comprehensive series creates intense emotions through diverse lighting effects in every desired coloured or white shade. Fitted with stainless steel frame and remote PSU, these versatile uplighters also come in a flush-mount full-glass version for an even more elegant and discreet layout. A robust drive-over version is suitable for installation in vehicular areas.

MAIN FEATURES

- Max. delivered lm output: 959 lm / 120 lm/W
- Max. size: (WxD) ø 100x65 mm / ø 3.9x2.6"
- Control system: DMX-RDM, DALI, ON-OFF, 0-10V, remote wireless data
- Small in-ground LED uplighters featuring either fixed or adjustable beam, available with stainless steel frame or full glass, in walk-over or drive-over versions


LED COLOUR CONFIGURATIONS







MOON RECESSED SERIES



FEATURES











OVER

Î

IK10









IP68





0.9 KG



OPTIONS







ANTI-SLIP

ETL PENDING

LED COLOUR CONFIGURATIONS



3000K













NATURAL

WARM WARM WHITE 2700K WHITE 3000K WHITE 4000K

MORE INFO

















CODES

AL5311 MOON RECESSED AL5325 MOON RECESSED ADJUSTABLE

PERFORMANCE	WATT	MAX LM OUTPUT	LM/WATT
MOON RECESSED RGBW	4.6	132	29
MOON RECESSED DW	4.6	211	46
MOON RECESSED W	7	839	120
MOON RECESSED US W	2.7	186	69
MOON REC. ADJUSTABLE RGBW	4.6	132	29
MOON REC. ADJUSTABLE DW	4.6	211	46
MOON REC. ADJUSTABLE W	8	959	120
MOON REC. ADJUSTABLE US W	2.7	186	69

RGBW/DW	W
_	6°
13°	18°
23°	25°
35°	35°
56°	50°
	- 13° 23° 35°



IN-GROUND UPLIGHTERS